

XX

## INTRODUCTION

## PREFACE

## PREAMBLE: FIELD RESEARCH IN JAPAN

1. PREPARATORY AND AUXILIARY PROCESSES
  - 1.1. Calculating the number and the length of elements
  - 1.2. Warping and mounting
    - 1.2.1. Mounting by hitching or knotting the elements to a dowel or a string
    - 1.2.2. Mounting by applying auxiliary threads
  - 1.3. Fastening the mounted set of elements
  - 1.4. How to deal with exceptionally long elements
  - 1.5. Auxiliary tools and preparatory processes in a Japanese workshop
  - 1.6. Some general considerations regarding the use of hands and fingers
  - 1.7. Some useful knots
    - 1.7.1. The slipped weaver's knot A very short warp
    - 1.7.2. The square knot Mounting without auxiliary threads
    - 1.7.3. The constrictor knot
  - 1.8. Interworking a set of elements with free ends
    - 1.8.1. The three-strand braid
    - 1.8.2. A larger number of elements
  - 1.9. Disentangling the ends
  - 1.10. Finishing processes
2. BALANCED PLAIN INTERLACING
  - 2.1. General rules for interworking a set of elements with free ends
    - 2.1.1. The basic laws for flat braids
  - 2.2. Braiding with strips
    - 2.2.1. Starting on a transverse edge
    - 2.2.2. Folding the strips at the selvages
    - 2.2.3. Joining braids selvedge to selvedge with an auxiliary thread
    - 2.2.4. Dividing a braid into two or more separate braids
    - 2.2.5. Forming an angle
    - 2.2.6. Forming a tube
    - 2.2.7. Adding elements
    - 2.2.8. Doubling the structure or forming three-dimensional corners
  - 2.3. Straw braiding in Europe
  - 2.4. Extended plain interlacing
  - 2.5. Balanced plain interlacing with bundled elements
  - 2.6. Colour effects
  - 2.7. Linkings applied to modify the colour-effect
  - 2.8. Beaded Braids
  - 2.9. Double-cloth balanced plain interlacing and twining
  - 2.10. Large fabrics
3. THE CRAMMING-SPACING EFFECT
4. BALANCED RIBBING
  - 4.1. Planning a design
  - 4.2. Thread-calculation
  - 4.3. Mounting
  - 4.4. Interworking
  - 4.5. The selvages
  - 4.6. Colour-effects
    - 4.6.1. Colours arranged one by one
    - 4.6.2. Units of different colours
  - 4.7. Further Developments
    - 4.7.1. Occasional linkings used to influence the colour-effect

- 4.7.3. Enlarged units
  5. FLAT ANGLED RIBBING WITH PAIRED ELEMENTS IN THE CONCEALED COURSE
    - 5.1. Ribbed interlacing
    - 5.2. Ribbed twining
    - 5.3. Different methods of working flat-angled ribbing in two sections
    - 5.4. The starting edge
    - 5.5. Twined oblique interlacing with spaced elements in the concealed course
      - 5.6. Shaping the fabrics
      - 5.7. Forming angles with one single band
        - 5.7.1. A blunt angle
        - 5.7.2. An acute angle
      - 5.7.3. Interpolating wedges in balanced ribbing
      - 5.7.4. Three-dimensional shaping
      - 5.7.5. Curving a braid consisting of two sections of flat-angled ribbing
      - 5.7.6. Increasing the width of a fabric
    - 5.8. Working with several groups
    - 5.9. Occasional rows of twining
    - 5.10. Colour-effects in ribbed oblique interlacing and twining
  6. INVERTING THE SLANT OF THE PASSAGES
    - 6.1. One inversion at midpoint
      - 6.1.1. Forcing the concealed elements
      - 6.1.2. Interpolating irregular passages
    - 6.2. Repeated inversions worked in two sections
    - 6.3. Colour-effects
    - 6.4. Japanese Kara-kumi
    - 6.5. Peruvian braids with inversions
  7. THE ARROW-PATTERN
    - 7.1. The Assumption-sashes
    - 7.2. The braids of the Eastern American Indians
    - 7.3. The working-arrangement of the Quebec braiders
    - 7.4. Technical description of the linkings
    - 7.5. The designs
  8. INTRODUCTION OF THE TRACK-PLANS
    - 8.1. Abstract approach
    - 8.2. Romantic approach
  9. THE INDUSTRIAL BRAIDING MACHINE
    - 9.1. History
    - 9.2. The principle
    - 9.3. A comparison of machine-braiding and hand-braiding
  10. TWILL OBLIQUE INTERLACING FLAT AND TUBULAR - WORKED WITH FREE ENDS
    - 10.1. Flat twill oblique interlacing with longitudinal ridges
      - 10.1.1. The total number of elements making up a flat braid
      - 10.1.2. Two-eyed tracks
      - 10.1.3. Tracks with four or any even number of eyes
      - 10.1.4. Tracks with three or any odd number of eyes
      - 10.1.5. Colour-effects
      - 10.1.6. Starting a twill oblique interlacing on a transverse edge
      - 10.1.7. The cramming-spacing effect in twill oblique interlacing
      - 10.1.8. Combined twill and extended plain oblique interlacing
    - 10.2. Tubular twill oblique interlacing
      - 10.2.1. Longitudinal ridges

Some more variants of balanced ribbing

- 10.2.2. Colour-effects in tubular braids
- 10.2.3. The total number of elements making up a tubular braid
- 10.2.4. Practical remarks
- 10.2.5. Some tubular braids
- 10.2.6. Combined flat and tubular interlacing
- 10.3. Flat and tubular twill oblique interlacing with transverse ridges
- 10.4. Combined longitudinal and transverse ridges
- 10.5. Two peculiar methods of producing the two-ridge braid
- 10.5.1. Braids worked in one single length
- 10.5.2. Braids inside of leather bands

#### 11. BRAIDING WITH COMPLEMENTARY PASSAGES

- 11.1. Colour-effects
- 11.2. Basic method
- 11.3. The diagrams
- 11.4. The passages of the active elements
- 11.5. The outward-shifting of the passive elements
- 11.6. The process of sorting out two distinct series
- 11.7. The size and the colour of the ridges
- 11.8. The allotment of the elements to distinct tracks
- 11.9. Countered passages of rotational symmetry
- 11.10. Sequences of three and of four steps
- 11.11. Two-layer plain oblique interlacing exchanging faces between each crossing
- 11.12. Enlarging the ridges of the outward-tending course
- 11.13. Abnormal central ridges
- 11.14. Working with an odd number of elements
- 11.15. One-step passages
- 11.16. Conclusion

#### 12. PLY SPLITTING

- 12.1. General description of the working-principle
- 12.2. Advantages and limitations of the method
- 12.3. The material
- 12A. WARP-TWINED FABRICS WITH A DIFFERENTIATED WEFT
- 12B. FREE-FORM OBJECTS
- 12C. OBLIQUE INTERWORKING BY PLY-SPLITTING
- 12C.1. Oblique twining
- 12C.2. Double-cloth plain oblique interlacing with interchanging layers
- 12C.3. Mixed oblique interlacing and oblique twining
- 12C.4. Oblique intertwinning
- 12D. "TWINED LINKING" 12.4.5. Twill
- 12.4. Conclusion
- 12E. A JAPANESE LOOM PRODUCING WARP-TWINED FABRICS BY PLY-SPLITTING

#### 13. SPRANG

- 13.1. The Sprang-principle
- 13.2. The working-method
- 13.3. The characteristics of the structures
- 13.4. Some remarks on the term "Sprang"
- 13.5. Sprang on oblique fells?

#### 14. LOOP-MANIPULATION

- 14.1. General remarks
- 14.2. Preparing the loops
- 14A. LOOP-MANIPULATED WARP-TWINING
- 14A.1. The "guilloche"
- 14A.2. Tubular twining
- 14A.3. Fringe-trimming
- 14A.4. Edge-trimming
- 14A.5. Colour effects

- 14A.6. Cross-relations
- 14A.7. Warp-twining with several loops aligned in sequence
- 14A.8. The fringed aprons of Roumania
- 14B. LOOP-MANIPULATION - OBLIQUE INTERLACING
- 14B.1. The 17th century pattern-books
- 14B.2. Twill oblique interlacing
- 14B.2.1. Handling the loops
- 14B.2.2. One person working
- 14B.2.3. Two or more people cooperating
- 14B.2.4. Colour-effects
- 14B.2.5. Fancy designs based on twill
- 14B.3. "The Arme Beadth"
- 14B.3.1. Four people cooperating
- 14B.3.2. Cross-relation
- 14B.4. Plain oblique interlacing
- 14B.4.1. Two workers cooperating
- 14B.4.2. Colour-effects
- 14B.4.3. Double-cloth plain oblique interlacing with interchanging layers
- 14B.4.4. Drafting designs
- 14B.5. Identification and distribution
- 14B.6. "Unorthodox" patterns
- 14B.6.1. A prominent "unorthodox" pattern
- 14B.6.2. Distribution
- 14B.6.3. A degenerate form of loop-manipulation
- 14C. TWO OR MORE LOOPS ALIGNED IN SEQUENCE ON INDIVIDUAL FINGERS
- 14C.1. Two ridges
- 14C.2. Four ridges
- 14C.3. Eight ridges

#### 14D. "RECIPROCAL BRAIDING"

#### 15. TAKA-DAI

- 15.1. Range of possibilities
- 15.2. Description of the apparatus
- 15.3. Mounting the set of elements
- 15.4. The working-process
- 15.5. Working on one plane
- 15.5.1. Plain oblique interlacing
- 15.5.2. Ribbed interlacing
- 15.5.3. Twill
- 15.5.4. Linkings applied to influence the colour-effect
- 15.6. Working on two planes
- 15.6.1. The selvedge-connections
- 15.6.2. Some patterns worked on two planes
- 15.6.3. Swapping bobbins
- 15.6.4. Double-cloth oblique interlacing giving motifs by interchanging layers
- 15.6.5. Two layers forming diamonds by exchanging faces
- 15.6.6. "Kikko" - a definite colour-effect produced by two layers exchanging faces

#### 16. TABLE-SUPPORTED BRAIDING

- 16A. JAPANESE MARU-DAI AND KAKKU-DAI
- 16A.1. Upward braiding
- 16A.2. Downward braiding
- 16A.3. The core
- 16A.4. The counterweight
- 16A.5. Shape and size of the table-top
- 16A.6. Mounting the set of elements
- 16A.7. The configuration of the threads on the table-top

16A.8. The process of braiding  
 16A.9. The effect of upward and downward braiding  
 16A.10. The braiding-material  
 16A.11. The twist  
 16A.12. Colour-effects  
 16A.13. The patterns  
 16A.13.1. Round tracks            16A.13.4. Oval tracks overlapping centrally  
 16A.13.2. Two-eyed tracks       same rotation throughout  
 16A.13.3. Three-eyed tracks  
 16A.13.4. Two antique braids of extremely complex structure  
 16A.14. Oblique twining on Maru-Dai  
 16B. HAIR-BRAIDING  
 16B.1. Some general words on hair-work  
 16B.2. The tools used for hair-braiding  
 16B.3. Preparing and mounting the set of elements  
 16B.4. After-treatment  
 16B.5. The pattern-books  
 16B.6. The peculiarities of the patterns  
 16B.6.1. Flat braids  
 16B.6.2. Solid braids made up by round tracks  
 16B.6.3. Rectangular braids  
 16B.6.4. Three-eyed tracks  
 16B.6.5. Coiled tracks  
 16B.6.6. Tubular braids  
 16C. THE HYPERBOLICAL PROJECTS OF ASHLEY  
 16D. THE FOUR STRAND SQUARE BRAID WORKED ON A TRANSVERSE FELL  
 BUT WITHOUT SUPPORTING TABLE  
 16D.1. In vertical position  
 16D.2. In horizontal position

17. NAIKI-DAI, A JAPANESE MACHINE DESIGNED TO PRODUCE TUBULAR BRAIDS  
 17.1. History  
 17.2. Description  
 17.3. Mounting the set of elements  
 17.4. The working-process  
 17.5. Twill oblique interlacing with transversal ridges  
 17.6. Twill interlacing with longitudinal ridges  
 17.7. Flat braids  
 17.8. Concluding remarks  
 17.9. Cross-connection

18. FIST-SUPPORTED, FINGER-SECURED BRAIDING  
 18A. SOLID BRAIDS  
 18A.1. Starting a braid  
 18A.2. Braiding-movements  
 18A.3. The properties of the structure  
 18A.4. The properties of the method  
 18A.5. Colour-effects  
 18A.6. The same twining-twist in all cords  
 18A.7. Reversing the twining-twist  
 18A.8. Other track-plans  
 18A.9. Flat braids  
 18A.10. Working with a core  
 18A.11. Figurative motifs produced by substituting threads  
 18A.12. Certain tracks appearing and disappearing temporarily  
 18A.13. Exchanging elements between tracks  
 18A.14. Three-span floats  
 18A.15. Two-eyed tracks  
 18A.16. Three-eyed tracks  
 18A.17. Distribution  
 18A.18. A few words on slings

18B. TUBULAR BRAIDS IN PLAIN AND TWILL INTERLACING  
 18B.1. Plain interlacing  
 18B.2. Twill interlacing with transverse ridges  
 18C. TUBULAR LINKING  
 18C.1. Two-span floats  
 18C.2. Substituting threads of contrasting colour  
 18C.3. Three or more-span floats  
 18C.4. A track with only one coil  
 18D. "CROWN SINNETS"

19. WARP-TWINING ON SPECIAL TOOLS  
 19A. AYA-TAKE DAI, A JAPANESE TOOL  
 19A.1. Description of the tool  
 19A.2. Changing the shed  
 19A.3. The weft  
 19A.4. Wings with two ledges  
 19A.5. Wings with three ledges  
 19A.6. Oblique intertwining  
 19B. THE "TRILLER" OR CORELL-MACHINE

20. HOW TO ANALYSE AND TO REPRESENT THE STRUCTURE OF A FINISHED BRAID  
 20.1. Initial remarks  
 20.2. Analysing a braid without unravelling it  
 20.3. Analysing a braid by disentangling it  
 20.4. Analysing a braid by removing the threads of certain tracks

21. CLASSIFICATION  
 21.2. Preliminary remarks  
 21A. CRITERIA FOR DESCRIBING AND CLASSIFYING THE FINISHED PRODUCTS  
 21B. FACTORS CHARACTERIZING THE WORKING-METHODS

22. THEORETICAL CONSIDERATIONS  
 22A. THE RANGE OF POSSIBILITIES PROPER TO DIFFERENT METHODS  
 22B. THE PROPERTIES OF WARP-WEFT INTERLACING, WARP-TWINING AND BRAIDING  
 22C. CONVERTING A WOVEN FABRIC INTO A FLAT OBLIQUE INTERLACEMENT

23. STRUCTURES WHICH COULD BE MISTAKEN FOR BRAIDS  
 23.1. Interconnected looping  
 23.2. Simple looping  
 23.3. Meshwork  
 23.4. Turks heads  
 23.5. Slit leather braids  
 23.6. Transposed warps  
 23.6. Soumak on tubular fabrics

24. DEALING WITH THE TWO-RIDGE FLAT AND THE FOUR-RIDGE "SQUARE" BRAID  
 24.1. How to pick up a "square" braid in disorder  
 24.2. Inverting the slant of the floats in a two-ridge braid  
 24.3. Combining two two-ridge braids

GLOSSARY

BIBLIOGRAPHY